

15 - 250 kVA DEDICATED NATURAL GAS G E N S E T



CPCB IV+ COMPLIANT

INDIA'S LARGEST FLEET OF GENSETS

Complying to India's Latest Emission Norms

BETTER POWER

limitless

TOMORROW

BETTER POWER



T O M O R R O W

A RICH HERITAGE OF OVER A CENTURY OF ENGINEERING EXCELLENCE.

Kirloskar power generating sets prioritize user experience, delivering exceptional features and benefits. Streamlined installation and enhanced dependability to expedited service, reduced maintenance costs, and optimized performance.



Kirloskar Powergen sets itself apart with groundbreaking engineering that establishes new industry benchmarks.

limitless potential, sustainable practices

Our state-of-the-art manufacturing facility embodies our commitment to sustainable practices. We partner with nature to power the facility itself, transforming waste into valuable resources. This focus on sustainability inspires both our workforce and surrounding communities. It's here, where cutting-edge technology meets exceptional skills, that we engineer solutions to empower limitless possibilities.



Discover our Plant with a QR Code Scan.

Specification Data of Gas Generator

Prime Rating at rated RPM (as per IS08528)		kVA	15 (ESP)	30	58.5	125	250
		kW	12	24	46.8	100	200
Genset Model			KG1-15AS NG1	KG4-30 WS NG1	KG1-62.5WS NG1	KG1-125WS NG1	KG1-250WS NG1
Frequency		Hz	50				
Power factor		lagging	0.8				
Voltage		V	230 (10) & 415 (30) 230 (10) & 415 (30) 415 (30)				
Steady-state Governing class (As per ISO 8528-5)			G3				
Noise level @ 75% rated load		dBA	< 75 @ 1 metrs				
Fuel consumption*	At 100 % Load	SCM	4	9.1	15.5	29.3	58.8
	At 75 % Load		3.5	7.1	12.5	23.2	47.2
	At 50 % Load		3.1	5.5	9.9	17.8	35.7
Inlet Gas pressure requirement		Min (Bar)	1	1	0.5	0.5	1
		Max (Bar)	4	4	4	4	4
Weight of genset with canopy (approx.)^	Dry	Kg	850	1100	2500	3600	5700
Overall dimensions of genset [#]	Length	mm	1740	2550	3325	3750	5100
	Width	mm	1050	1122	1225	1500	2000
	Height	mm	1410	1410	1800	1980	2410
Electrical battery starting voltage		Volts-DC	12	12	12	24	24
ENGINE							
Engine Model			HA294 NG1	3R1040NG1	6R1080 NG1	SL90TA NG1	DV8TA NG1
Rated output $^{\$}$		kW	15.1	30.1	61	114.7	228
		HP	20.5	42	83	156	310
No. of cylinder		Number	2	3	6	6	8
Cubic capacity		Ltrs.	1.89	3.1	6.49	8.86	15.92
Bore x Stroke		mm	100 x 120	105X20	105 x 125	118 x 135	130 x 150
Rated speed		RPM	1500				
Aspiration		NA/TC/TA	NA	NA	NA	TA	TA
Lube Oil change period		hrs.	500				
Lube oil sump capacity		Ltrs.	5	9	17	27	46
Coolant capacity		Ltrs.	NA	14	25	30	30
ALTERNATOR							
Insulation Class			Class H				
Alternator efficiency (at 100% load) 0.8 pf		%	86	82.2	91	92.5	92.5
Max voltage dip at full load 0.8 pf lag			< 20 %				
Max time to build up rated voltage at rated RPM			< 5 sec provided engine reach the rated speed				

ĸ∕rloskar

Minimum 70 methane number required Above specifications are subject to change without prior notice due to continuous technical development.



- Compliant to latest CPCB norms .
- Clean & Safe fuel
- Lower Operating cost н.
- No storage of fuel
- No handling / transportation of fuel. Online & Metered.
- Constant fuel quality & No adulteration.
- Electronic ECU & Carburation system .
- Remote monitoring system
- 1 year / 3000 hours warranty on complete Genset

Genset kVA 15-250 kVA Features



Prime rating and Stand-by rating

'Prime power' is designed for Unlimited hours, as compared to 'Emergency stand-by' designed for 200 hours in a year. Prime rated Gensets also permit 10% temporary overloading. Users need to carefully select the Genset rating to meet their requirement. Kirloskar offers Prime power as a standard offer. Contact Kirloskar for stand-by ratings.



Genset Monitoring at Your Finger Tips

Kirloskar gensets are enabled with Kirloskar remote monitoring system which shares Real Time Genset information and location services. It can be accessed via mobile device or desktop. Kirloskar remote monitoring system also highlights any parameter which needs special attention. These critical indication alerts are sent to user mobile via text message. It also alerts nearest services dealer in case of any emergency break-down.





On Board Diagnostics

Superior uptime. Genset comes with advanced diagnostic capabilities, this coupled with Kirloskar remote monitoring system provides real time monitoring of performance, emission and service critical parameters this helps for early diagnosis to fix the issues before system breakdown



Peace-of-mind Ownership

Kirloskar Gensets have always been preferred for their robust design and reliability over long usage life.

Kirloskar range carries the confidence of well-established and proven engine platforms. For compliance to revised CPCB norms, Kirloskar has carefully selected those technologies which not only retain, but enhance Gensets durability and on-site serviceability.

Thus, Kirloskar Gensets offer you many years of trouble-free performance; backed by the assurance of prompt support. Peace-of-mind driven by product reliability and low cost of ownership.



Alternator Features

Kirloskar Alternator is compact in design, rugged and best in class efficiency. Advanced Digital AVR improves the Voltage regulation and Response time.



Compact footprint

Kirloskar CPCB compliant Gensets are having compact footprint which results in space saving. CPCB compliant technology is upgraded by maintaining the compact footprint of Genset.

THE VERSATILE POWER GENERATOR SOLUTION











FOOD INDUSTRY

HEALTHCARE

HOSPITALITY

MANUFACTURING

REAL ESTATE



Glimpses CPCB IV+ Natural Gas Genset (15-250 kVA)

Engine

- Fully Electronic controlled Engine
 - Higher Cubic capacity results higher block loading
 - Electronic carburation system for correct AFR
 - Efficient HT Coil & Spark plugs for precise ignition
 - Best in class fuel efficiency

Exhaust System

- In built catalytic convertor as standard scope
 - Residential silencer with Protection
 cover
 - •Latest CPCB compliant exhaust System

Controller

- Microprocessor based KG 645 controller
- Graphical LCD display
- Best in class Monitoring & diagnostic capability
- Integrable with AMF & Communication compatible

🖲 Gas Train

- CPCB approved Gas train inside acoustic enclosure
- Consist of Gas filter, Solenoid & PRVs.
- Designed & developed to suit for genset application

EFFICIENCY• INTEGRATED

CPCBIV+

COMPLIANT

KIRLOSKAR NG GENSET15-250 kVA/22024062.

A KIRLOSKAR PROMISE



Mark bearing word 'Kirloskar' in any form as a suffix or prefix is owned by Kirloskar Proprietary L td. and Kirloskar Oil Engines L td. is the Permitted User. This Catalog is copyrighted and may not be reproduced in any form not even parts of it, without previous written permission by copyright owners, Kirloskar Oil Engines L td. Product improvement is a continuous process. Kindly contact Kirloskar Oil Engines Ltd. for latest information. Images are for illustration purposes only.